


Laser & Dimple Keys



TR-2050 PANTHER



TR-2050 PANTHER SX



TR-2050 PANTHER S

Electronic Set System	S	S	X
Manual Set System	X	X	S
Touch buttons	S	S	X
E.C.U. (electronic control unit)	S	S	X
Led lights	S	S	S
Standby system	S	S	X
Motion Sensitive Run	S	S	O
Horizontal suspension	S	S	X
Vertical suspension	S	S	S
X-axis stabilizer	S	S	X
Y-axis stabilizer	S	S	X
Z-axis stabilizer	S	S	S
Two different field on the clamp	X	S	X
Three different field on the clamp	S	X	S
+45/-45 degree-clamp	X	S	X
Electrostatic paint	S	S	S
ABS cover	S	S	S
0,01 sensitivity setting	S	S	S
Full protection from burr	S	S	S
Toolboxes	S	S	S
Standard carbide cutters	S	S	O
Standard HSS cutters	X	X	S
Universal tool holl (6mm)	S	S	S
Quiet engine (monophase)	S	S	S
Engine power 6000 d/d 150w	S	S	S
Maintenance free motor	S	S	S
Voltage (* Available 110v)	* 220-240v 50Hz	* 220-240v 50Hz	* 220-240v 50Hz
Dimension	34 x 30 x 42 (h,w,l)	36 x 30 x 42 (h,w,l)	34 x 30 x 42 (h,w,l)
Weight	22 kg	23 kg	20 kg